

Ice Warning System

FLASHING SIGN SYSTEM



ICE WARNING SYSTEM

Without warning, cold roads can turn into an invisible sheet of black ice. Icy roads are a contributing factor in crashes that lead to thousands of deaths and serious injuries per year. Bridge decks and overpasses tend to freeze before the normal roadways. TrafficCalm offers a real-time ice warning system to motorists that enhances the effectiveness of static warning signs and provides more meaningful information to the driver than 24/7 flashing signs or beacons.

The TrafficCalm Ice Warning System includes an infrared road surface temperature sensor that also monitors humidity and calculates the dew point. When thresholds are met where conditions are likely to form ice on the roadway, the ice sensor triggers the controller to wirelessly activate advance flashing LED warning signs. When those conditions are no longer met, the sign will automatically stop flashing.

FEATURES

Ice Sensor Features

The non-intrusive ice sensor provides surface temperature, air temperature, relative humidity, and dew point measurements. Premium materials are used to meet the demands of road weather professionals.

Highly Visible LED Warning Signs

TrafficCalm fully outlines the shape of the sign, with the most LEDs on the market, for a bright, visible sign in any environmental condition.

Retrofittable LED Rings

Utilize existing signage and add our LED sign rings for a more cost-effective solution.

Ruggedized Electronics

All electronics, radios, and LEDs are fully epoxy-potted and environmentally sealed. The entire pole with the sign, controller, solar panels, and batteries can be fully submerged and still operate.

Made in the USA

TrafficCalm Flashing Sign Systems are manufactured in the USA in an ISO 9001:2015 certified facility, meeting and exceeding industry and state testing requirements. TrafficCalm signs are unmatched in durability, brightness, accuracy, and ease of installation and use. Build America/Buy America Compliant.

TRAFFICALM.COM



SPECIFICATIONS

■ Road Temperature Sensor

Dimensions 8"x3"x3", 2 lbs.
170 mA current draw
Surface Temp Range: -40° to 85° C (-40° to +185° F)
Accuracy ±0.2° C at 32, ±0.5° C at all other temps
Field of View 12°
Measurement sample: 2 ft (0.6m) at 10ft (3m)

■ Controllers and Collaborators

Compatible with all Intelligent Controllers and Collaborators
All electronics hermetically potted for weatherproofness
Controller Mounting: Universal side of pole mounting bracket.
Top of pole kit available. Mounted behind solar panels or on pole-mounted cabinet
Inputs: : 2 per controller. Accepts dry contact closure from Road Temperature Sensor
Outputs: 2 per controller, 12W max out, multiple flash patterns, including RRFB and 1hz MUTCD compliant flash

■ Flashing LED Enhancement

MUTCD and FHWA Compliant for all Warning Signs
AVAILABLE SIGN RING SIZES
24" Ring uses qty 48 LEDs
30" Ring uses qty 64 LEDs
36" Ring uses qty 80 LEDs
48" Ring uses qty 112 LEDs
Exceeds SAE J595 Class 1 Intensity
Meets SAE J578 for chromaticity
Auto dimming
48-112 Amber LEDs (depending on sign size) for Redundancy and Uniform Light Distribution
LED rated lifetime of 100,000 hours

■ Environmental

-40° F to 165° F (-40° C to 74° C) system operating temperature
IP 68 Rated

■ Power Options

AC or Solar Power
Various solar and battery packages available based upon site locations
MPPT Solar Collection

DETAILS

■ Radio Collaboration

Secure Device-2-Device mesh-net radio network
Max 100ms wireless activation response time
1500'/457m of range, repeatable signal
2.4 GHz operating frequency
Unique Network ID clearly marked to speed installation
FCC, Type 1 approved

■ TrafficCalm® User Interface

WiFi Connectivity - No Internet Connection required. Configurable Flash Patterns
Wirelessly configures all devices on network
Unified Wireless Collaboration Activation & Setting
Configurable auto dimming and brightness profiles
Selectable flash duration: 1 second to 60 minutes
Integrated calendar time clock functionality
Built-in activation count & reporting
Compatible with TC-Remote Web Based Software

■ Warranty and Service

5-year limited warranty, 1 year on batteries
Unlimited tech support from US based factory technicians

