POWER ADAPTER 60w

RADAR SPEED SIGNS

POWER ADAPTER 120/277 VAC TO 12VDC

Our M75-ACPWR-U060 is designed to provide seamless installation with TraffiCalm's iQ900, iQ1200, and iQ1500 series signs.

FEATURES

Will work with IQ series 900, IQ series 1200, IQ series 1500,

Ruggedized Electronics

Built tougher than other systems on the market.

Made in the USA

TraffiCalm® Systems are manufactured in the USA in an ISO 9001:2015 certified facility, meeting and exceeding industry and state testing requirements. TraffiCalm® signs are unmatched in durability, brightness, accuracy and ease of installation and use. Build America/Buy America Compliant.

2024/09/16

+1855.738.2722 / sales@trafficalm.com / www.trafficalm.com



TRAFFICALM.COM







SPECIFICATIONS

POWER HANDLING

Universal Input Universal input, 100-277 VAC

Adjustable Output 12V DC PWM adjustable output

Protection Short circuit, overloading, and temperature protection.

Output 60W rated output

Grounding Grounding on driver and metal case

ENVIROMENTAL

Enclosure IP 68 Enclosure


Certification UL/ULC listed, Class P, type HL Rated, FCC Certified

Potted Electronics Potted electronics (hermetically sealed)

Operating Range -22° F to 140° F (-30° C to +60° C)

WARRANTY

3-year limited warranty excluding tires, 1-year on batteries





Integrates with TraffiCalm[™] iQ DFB signs iQ900, iQ1200 & iQ1500 *Note - (NOT compatible with iQ1800. See U200 series)



Mounting Plate Aluminum mounting plate

Hardware Stainless steel hardware where exposed

Weather Sealing All connections made with weather sealed wire capture connectors

Cable Harness Includes 5 foot (1.5m) compatible cable harness to connect to most TraffiCalm™ devices

Conduit and Compatible Fittings Includes 5 feet (1.5m) of weather tight conduit and compatible fittings

Mounting Brackets Includes round post mounting brackets for use with banding fasteners (not included)