

Solar / Battery Kit: 60 Watt / 70 Ah

SOLAR SOUTH ENHANCED KIT: M75-SLR70-000S



SOLAR/BATTERY KIT FOR TRAFFICALM® IQ SERIES RADAR SPEED SIGNS

TraffiCalm® solar/battery kits are specifically designed to be used on iQ Series Radar Speed Signs and provide year-round operation of the system. We have a multitude of solar/battery kits and will make sure you have the right sized system for your particular location using our sophisticated solar calculator that takes into account the amount of sunlight (insolation), temperature, and cloudy days experienced by month and the power draw of the particular model of Radar Speed Sign chosen.

FEATURES

Complete Kit

Includes the solar panel, panel rack, solar controller, battery box and heavy-duty mounting bracket, batteries, and conduit-enclosed wiring.

Easy Installation

No trenching required for cables. Utilizes industry standard hardware and mounting techniques. Consistent connectors and fasteners compatible with all TraffiCalm® Radar Speed Signs.

Environmentally Friendly

Utilizing solar energy combined with the low-power draw of Light Emitting Diodes (LEDs) in TraffiCalm® Radar Speed Signs, these solar kits are the environmental choice for our planet, while helping make our roadways safer.

3-Year Warranty

3-year limited warranty on the solar kit, with 1 year on the batteries.

Made in the USA

TraffiCalm® Solar/battery kits are manufactured in the USA in an ISO 9001:2015 certified facility. In addition we provide you unlimited technical phone support for the life of the unit. Build America/Buy America Compliant.

TRAFFICALM.COM



SPECIFICATIONS

PHYSICAL DESCRIPTIONS

- Mounting: Universal bracket accommodates most industry standard round or square posts of suitable load rating

- NEMA 3R enclosure

- All electronics potted for weatherproofness

- Stainless fasteners used for corrosion resistance

- Battery Box Dimensions: 12" h x 12" w x 10" d
[30.48 cm x 30.48 cm x 25.4 cm]

- Solar Panel Dimensions: 30.47" l x 26.57" w x 1.18" d
[77.39 cm x 67.49 cm x 3 cm]

- Total System Weight: 94 lbs [42.64 kg], includes qty 2 - 35Ah batteries, battery box w/ contents, solar panel, and solar panel rack

CONSTRUCTION

- 14 gauge carbon steel Weatherproof NEMA 3R battery housing

- Standard, flat mount brackets

- Provisions for padlocking

- Replacement keys available upon request

- Standard powder coat gray color polyester finish [additional colors optional]

SOLAR PANEL POWER SPECS

- Maximum Power (PMax): 60W
- Voltage at PMax (Vmp): 17.2V
- Current at PMax (Imp): 3.49A

- Open Circuit Voltage (Voc): 21.6V
- Short-Circuit Current (Isc): 3.86A

- Temp. Coefficient of Voc: $-[80 \pm 10] \text{mV}/^\circ\text{C}$
- Temp. Coefficient of Isc: $(0.065 \pm 0.015)\%/^\circ\text{C}$
- Temp. Coefficient of power: $-(0.5 \pm 0.05)\%/^\circ\text{C}$

- NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s): 47±2°C
- Operating Temperature: -40°F to +85°F [-40°C to +85°C]

- Maximum system voltage: 60VDC, 1500 watts

- Power tolerance: ± 5%

BATTERY SPECS

- M75-SLR70-000S includes qty 2 batteries

- 12V AGM valve regulated, spill proof, high energy density, DOT approved for transport. Nominal Voltage: 12V (6Cells). Nominal Capacity: 20-hr. (1.75A to 10.50V): 35Ah

- Approx. Weight: 24.7 lbs each

- Energy Density: 1.70 W-h/in³

- Internal Resistance: 8 milliohms

- Max Discharge Current (7 Min.): 105.0 amperes

- Operating Temperature: Charge: -4°F to 122°F [-20° C to 50° C], Discharge: -40°F to 140°F [-40° C to 60°C]

- Dimensions: 7.72" l x 5.14" w x 6.22" h [19.61 cm x 13.06 cm x 15.8 cm]

WARRANTY

- 3 year warranty, 1 year on batteries

- Unlimited technical support

- Made in America

